Yealink

STOCK SYMBOL: 300628



Yealink Meeting PRODUCT MANUAL

Yealink Meeting

Yealink Meeting is a distributed cloud-based service platform tailored for multi-way video conferencing collaboration. As a powerful all-in-one service platform, Yealink Meeting not only brings MCU, registrar server, traversal server, meeting management server, meeting control server, enterprise directory server, GK&H.460 server and so on together, but also seamlessly integrates with s a whole series of video conferencing products. Being in an advanced distributed architecture, Yealink Meeting is distributed with multiple service nodes around the world with better expandability, and it also owns multi-point and multi-machine hot standby which are functioned as a failover mecha-nism to provide reliability in system configuration. Characterized with rich functions, it provides 1080P full encoding and decoding capability and multi-groups and large-capacity conferences, scheduled conference, meet-now conference, etc. Ease-of-use, simple deployment, easy maintenance, good security and reliability, Yealink Meeting delivers the specific solutions to address your unique needs for an enterprise or a service provider.

Key Features

- All-in-one, brings MCU, registrar, directory, traversal server, meeting management server and GK&H.460 server together
- · Advanced cloud-based architecture with multiple worldwide service nodes
- 1080P full encoding and decoding capability
- · Supports a Standard SIP/H.323 Endpoint dial server IP to join meeting directly
- · Interoperability with Microsoft Teams for audio, video, and content sharing
- · Supports RTMP Live, a large number of participants can watch the live broadcast simultaneously
- ICE/TURN/STUN/NAT/H.460, deployment across the network
- · Supports scheduling meeting through Outlook or Web or Yealink Client
- Supports multiple conference modes: P2P, scheduled conference, instant meeting, Virtual meeting room, and supports a variety of layout modes includes
- speaker mode, picture in picture mode, gallery mode
- TLS/SRTP/HTTPS and dynamic password ensures the security of conference
- · Deeply integrated with Yealink VC devices, support conference reminder and one-touch conference access
- · Support enterprise reports and statistics, data visualization analysis

Specifications

System Services Modules	 MCU Registrar Server Traversal Server Enterprise Directory Server 	 Meeting Management Server H.323/SIP Trunk Server RTMP Live Server Teleconferencing Server 		
Audio And Video Features	 Dual 1080P30: video + content sharing Video resolution: 1080P, 720P, 360P, 4CIF, CIF Video codec: H.264 High Profile, H.264, H.263+, H.263, VP8 Audio codec: Yealink ARES, Opus, G.722.1C, G.722.1, G.722, G.711(a/u), G.729, AAC-LC Forward Error Correction (FEC), anti 70% audio packet loss and 30% video packet loss Bandwidth dynamic adaptive adjustment 			
MCU	 1080P30 full HD video encoding and decoding Mixed protocols, bandwidth, resolution and frame rate Interactive broadcasting conference, up to 1000 participants in every single conference Unlimited group conference Flexible layouts: Gallery Mode NxN (N=2, 3, 4, 5, 6, 7), Speaker Mode 1+N (N=0, 4, 7, 9, 12, 16, 20) and Picture in Picture Mode Gallery Mode and Speaker Mode layouts dynamically scale as more participants join Set as spotlight Voice activated speaker 			
	 Configurable video carousel Permanent/dynamic conference ID and password without conflict 			

Registrar and Traversal	 Configurable permanent Virtual Meeting R Interactive Voice Response (IVR) Join Cloud video conference via Teams Cl Enterprise self-management Up to 10,000 accounts Import and export accounts in batch Organizational structure Group management for user accounts 		ss the enterprises port resources consumption ase synchronization
Meeting Management	 Support scheduling meeting via Web or O Room system account associated with me Support Speaker Mode, Gallery Mode and Create instant conference by one-click (M Automatic synchronization of scheduled or Conference reminder and one-touch conference via standard Automatic dialing Register and join conference via standard Join conference via mobile phone and des Share conference information via QR Code 	eting room I Picture in Picture Mode eet Now) onfer-ence to Yealink video endpoints erence access SIP/H.323 devices sktop phone	
Meeting Control	 Personal layout and broadcasting layout Invite/remove participants Lock/unlock and end conference Conference lobby Mute/unmute audio and video Block/unblock audio and video Apply for speaking in meeting Set as spotlight Rename Remote camera control (FECC) Participants'role free switching Invite contacts, H.323/SIP/Teams device Manual/automatic roll call and export recording Fast call Conference banner Dynamic/static subtitle messaging to individe the participant name and statute call statistics 	idual or all parties	
Value-Added Services	 Teleconference service Cloud storage services Live broadcast service Support Teams service 		
System Management	 Email notification Link your cell phone number to your acco Meeting Statistics: Conference details and Conference parameters configuration Open API H.323/SIP 		
Network And Security	 H.323/SIP Dual stream protocol: H.239/BFCP SRTP/TLS, AES (256) encryption Meeting password and troubleshooting me HTTPS Web Server SSH remote secure access Double-layer firewall Intrusion Detection System (IDS) Real-time network monitoring 	echanism	



• Vulnerability scan & bug fix

• Anti-virus

Yealink

YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD. Web: www.yealinkmeeting.com Addr: No.1 Ling-Xia North Road, High Tech Park, Huli District, Xiamen, Fujian, P.R. China Copyright©2020Yealink Inc. All right reserved.